

- Indpro Hydraulic ATW Series
- Indpro Hydraulic HX Series
- Indpro Hydraulic NZ Series

INDPRO HYDRAULIC ATW SERIES are premium quality anti-wear hydraulic oils formulated from highest quality basestocks and advanced additive technology to provide a superior level of system cleanliness, excellent filterability, thin oil-film rust inhibition, wear protection and water separation. They are available in ISO viscosity grades 32, 46, 68, & 100 and recommended for the lubrication of conventional high pressure, high output hydraulic systems. They meet or exceed the following industry specifications: Denison HF-O, HF-1 & HF-2, Vickers M2590-S, I-286-S, Cincinnati Milacron P-68, P-69, P-70, US Steel P-127, P-136 & DIN 51524 Pt 2 & 3.

INDPRO HYDRAULIC HX SERIES are quality anti-wear hydraulic oils designed to provide a high degree of system cleanliness, good filterability, rust inhibition, wear protection and excellent water separation. They are available in ISO viscosity grades 32, 46, 68, & 100 and recommended for the lubrication of conventional hydraulic systems.

INDPRO HYDRAULIC NZ SERIES are premium quality, non-zinc/anti-wear hydraulic oils designed to provide a high degree of system cleanliness, excellent filterability, rust inhibition, wear protection and outstanding water separation. They are available in ISO viscosity grades 32, 46, 68, & 100 and are recommended for the lubrication of hydraulic pumps and systems, stationary and mobile operating under normal to severe conditions where an anti-wear oil is required. They meet or exceed the following industry specifications: Denison Filterability TP 02100, Vickers M2590-S, I-286-S, US Steel P-126 & 7, P-136, DIN 51524 Pt 2 & 3 and AFNOR NF E48-603 (HM, HV).

---